

BEKOMAT® Product Selector Chart

Compressor HP	Compressor SCFM	After Cooler	Wet Receiver Tank	Pre-Filter	Refrigerant Dryer	Post-Filter	Dry Receiver Tank
20	100	31	31	31	31	31	31
40	180	32	32	31	31	31	31
50	225	32	32	31	32	31	32
60	270	33	33	31	32	31	32
75	338	33	33	31	32	31	32
100	500	33	33	31	32	31	32
125	563	13	13	31	33	31	33
150	675	13	13	31	33	31	33
175	788	13	13	31	33	31	33
200	900	13	13	31	33	31	33
250	1125	13	13	32	13	32	13
300	1300	13	13	32	13	32	13
400	1800	14	14	32	13	32	13
500	2250	14	14	32	13	32	13
750	3375	14	14	33	14	33	14
1000	5000	14	14	33	14	33	14
1250	5625	16	16	13	14	13	14
1500	6750	16	16	13	14	13	14
1750	7875	16	16	13	14	13	14
2000	9000	16	16	13	14	13	14
2500	11250	16	16	13	16	13	16
3000	13500	16	16	13	16	13	16
4000	18000	16	16	14	16	14	16
5000	22500	16	16	14	16	14	16

To use the BEKOMAT® Product Selection Chart, first locate either your compressor horsepower (for multiple compressors use the total system horsepower) or the net flow rate of your compressed air system. Follow the row to the right and locate the column with the appropriate installation point for your application (i.e wet receiver tank) and you will instantly know the correct BEKOMAT® model size for your application and installation point.

For extremely corrosive applications where excessive amounts of rust, scale or particles are present please contact your BEKO representative for special installation instructions.

Capacity tests and our long-term experience have enabled us to make locational adjustments to our capacity figures by taking global climate data into account. Therefore, if you feel that your regional location may have an impact on the application or installation, please contact your BEKO representative for details.

	Multi - Voltage	
	18 - 72 VDC / 24 - 48 VAC	100 - 125 VDC / 95 - 240 VAC
BEKOMAT® 31 / 32 / 33	o	•

	230 VAC	115 VAC	110 VAC	48 VAC	24 VAC	24 VDC
BEKOMAT® 12 / 13 / 14 / 16	o	•	-	o	o	o
BEKOMAT® 3 / 6	o	-	•	o	o	o

o optional • standard - not available

Certain voltage/drain model combinations are not available with NPT thread. All alternating voltages (AC) are operational with 50 and 60 Hz. All 110 and 115 Vac BEKOMAT® drains include 6 ft. UL/CSA approved cable and plug as standard.

Product Code Key

oil and oil-free condensate all standard models	A
special gas application CO variants	B
highly corrosive applications stainless steel variants	C